

















در راستای توسعه دامنه خدمات و پاسخ وگویی بهتر به نیاز مشتریان بالادستی صنایع نفت و گاز در حال حاضر تامین بخش اعظمی از تجهیزات و ماشین آلات سرچاهی، درون چاهی و حفاری مطابق با استنادارد های بین المللی و نیاز صعنت نفت میسر گردیده است.

موتورهای درون چاهی((Down Hole Motors و دستگاه اندازگیری حفاری(MWD)) توانایی حفاری با توان بالا و ساعت های بسیاری را دارا می باشد. که به شرح روبرو می باشد:



item	Description	Tools size available
1	Mwd/GR	9 %", 6 %" 4 %" 3 %"
2	Down hole Motor	17 %",9 %", 6 %" 4 %", 3 %"
3	NMDC/PONY NMDC	9 %", 6 %" 4 %", 3 %"
4	HWDP	5", 3 ½"
5	Drilling Jar	9 %", 6 %" 4 %", 3 %"
6	Stablizer	17 %",9 %", 6 %" 4 %" , 3 %"
7	хо	17 %",9 %", 6 %" 4 %", 3 %"
8	Float Sub	9%",6%" 4%",3%"



MWD SPECIFICATION

MWD Specification				
Directional Measurement	Measuring Range	Measuring Accuracy		
Inclination angle	0°-180°	+/- 0.1°		
Azimuth Angle	0°-360°	±(Inc>9") ±1.5"(Inc>5"-9") ±2"(INC<5")		
Tool face Angle	0°-360°	±1°		
Maximum Allowable Vibration	20g@5-100Hzsin			
Operating Temperature	0°C-150°C			
Maximum Pressure	100Mpa			
Size	ø47.6mm×1829mm			
Meantime Between Failures	Not less than 1000h			

Gama Specification			
Parameter Name	Measuring Range		
Detection range	0-500 API		
Measuring Accuracy	±3API		
Sensitivity	2.0-2.5API		
Operating Temperature	0°C - 150C°		
Resist compression	100MPA		
Shock Resistance	1000g@0.5ms		
Shake	30g@5-300Hzsin		
Size	ø47.6mm×1829mm		



DD SERVICES

MWD SERVICES

PETRO ALMAS KISH offers a full range of MWD services for accurate and cost-effective. Real-time directional surveying MWD is recommended for applications such as drilling the Directional, PETRO ALMAS KISH stocks MWD systems for use in E/Y Einch to E/I IYinch hole size and can provide equipment for other hole sizes as required.

DOWN-HOLE MOTORS

PETRO ALMAS KISH carries a full range of tool sizes from Y/1 Tinches OD through to $\Lambda/0$ 9inches OD with T/0 to Λ/V lobe configurations.





